



ALTUROS
destinations

USER MANUAL

English 2021/08



Alturos Photoprint

LEGAL NOTICE**ALTUROS DESTINATIONS GMBH**

Lakeside B03
9020 Klagenfurt, Austria
Phone: +43 463 249 445
Fax: +43 463 249445-102
Mail: office@alturos.com

ALTUROS DESTINATIONS AG

Churerstrasse 54
8808 Pfäffikon SZ, Switzerland
Phone: +41 55 588 0175
Mail: office@alturos.com

ALTUROS DESTINATIONS SAS

42 chemin des Liquines
73100 Tresserve, France
Téléphone : +33 09 83 28 55 44
E-Mail : office@alturos.com

DISCLAIMER OF LIABILITY**© ALTUROS DESTINATIONS GMBH**

All rights reserved. All information in this documentation is protected by copyright. All parts of this documentation are the intellectual property of ALTUROS DESTINATIONS GMBH. The use, in particular the passing on, reproduction, publication and provision of this documentation, including copying, even in part, as well as its imitation, processing or exploitation requires the express consent of ALTUROS.

ALTUROS reserves the right to make changes to the specifications and other information in this documentation without prior notice.

The greatest care has been taken in the compilation of illustrations and texts. However, possible errors cannot be excluded. No responsibility is taken for the compilation.

Content

1	General Information	4
1.1	DOCUMENTATION NOTES	4
1.2	STORAGE OF DOCUMENTS	4
1.3	COPYRIGHT	4
1.4	SYMBOLS IN THIS MANUAL	5
1.4.1	Used pictograms	5
1.4.2	Used warning labels	6
1.5	CONSUMABLES / SPARE PARTS	7
2	Safety	8
2.1	WARRANTY AND LIABILITY	8
2.2	APPROPRIATE USE	9
2.3	MODIFICATIONS AND CHANGES TO THE DEVICE	9
2.4	STAFF REQUIREMENTS	10
2.5	SAFETY AT WORK	11
3	Technical specifications	12
3.1	OVERVIEW	12
3.2	DATA TABLE TERMINAL	13
3.3	DATA TABLE PHOTO PICKUP MODUL	15
3.4	TYPE PLATE	16
4	Operation terminal	17
4.1	OPENING THE DEVICE	17
4.2	CLOSE THE DEVICE	19
4.3	SWITCHING THE DEVICE ON AND OFF	20
4.4	CHANGING THE THERMAL PAPER ROLL	21
4.4.1	Opening the door	21
4.4.2	Remove empty roll	22
4.4.3	Open printer flap	23
4.4.4	Closing the printer flap	24
4.4.5	Inserting the new thermoroll	25
4.4.6	Insert paper	26
4.4.7	Remove test print section	27
4.4.8	Close the door	28
4.5	MAINTENANCE SCREEN	29
4.5.1	Language	29
4.5.2	System data	29
4.5.3	Network configuration	30
4.5.4	Out of Order mode	31

4.5.5	Test print.....	31
4.5.6	Barcode Reader Test.....	32
4.5.7	RFID Reader Test	32
4.6	REMOTE ACCESS	33
5	Operation Photo Pickup Modul	34
5.1	OPEN THE DEVICE	34
5.2	CLOSE THE DEVICE	36
5.3	LOADING PAPER AND RIBBON	37
5.3.1	Open the device.....	37
5.3.2	Pulling out the printer.....	37
5.4	MAINTENANCE SCREEN	39
5.4.1	System data	40
5.4.2	Language.....	40
5.4.3	Test print.....	41
5.4.4	Out of Order mode	41
5.4.5	Information Photoprint	42
5.5	CLEANING	43
6	Troubleshooting.....	44
7	Value preservation	46
8	Support.....	46
9	Disassembly & disposal	47
9.1	DISASSEMBLY	47
9.2	DISPOSAL.....	47

1 General Information

1.1 Documentation notes

The following instructions are intended as a guide to the overall documentation.

These user manuals describe how installation, commissioning, service and repair work can be carried out by trained personnel.

Special tools are required to perform these activities.

1.2 Storage of documents

Keep this user manual and all other applicable documents in a safe place so that they are available when needed.

1.3 Copyright









The operating instructions must be treated confidentially. It is intended exclusively for the persons working on and with the device. All information, texts, drawings, pictures and other representations are protected by copyright and are subject to further industrial property rights.





Any misuse is liable to prosecution. Passing on to third parties as well as reproduction in any kind and form - even in extracts - as well as the exploitation or communication of the content is not permitted without the written consent of Alturos Destinations.

Contraventions obligate to compensation for damages. Further claims are reserved. We reserve all rights to exercise industrial property rights.







1.4 Symbols in this manual

1.4.1 USED PICTOGRAMS

	Note: <i>Observe usage!</i>
	Note: <i>Avoid damage!</i>
	Note: <i>Correct use!</i>
	Note: <i>Wrong use!</i>
	Hint: <i>To facilitate the procedure</i>
	Information
	Torque
	Sustainability

	NOTICE means, that damage to objects can occur.
	CAUTION means, that minor to medium personal injuries can occur.
	WARNING means, that serious to life-threatening personal injuries can occur.
	DANGER means, that serious to life-threatening personal injuries will occur.

1.4.2 USED WARNINGLABELS

	Hazard: <i>Warnings of injuries.</i>
	Hazard: <i>Hazards due to electrical voltage. Do not touch these parts until the power supply to the device has been disconnected.</i>
	Hazard: <i>Hazards due to heat development. Do not touch these parts when the device is switched on. It is essential to let them cool down before touching them.</i>
	Caution: <i>Electrostatically sensitive components. Ensuring electrostatic discharge before contact by earthing, to avoid ESD damage.</i>
	Warning: <i>Risks due to optical radiation. Avoid direct eye contact. Optical radiation can damage your eyesight.</i>
	Warning: <i>Lifting heavy objects causes strain on the human movement and support apparatus.</i>

1.5 Consumables / spare parts

NOTICE

Incorrect or defective consumables or spare parts can lead to damage, malfunction or total failure of the device!

The use of non-recommended consumables will void all warranty, service, compensation and liability claims against the manufacturer or its authorised representatives, dealers and agents.



The consumables recommended for use are listed under point Fehler! Verweisquelle konnte nicht gefunden werden. (Technical Data) or must be approved by Alturos.

2 Safety

2.1 Warranty and liability

The warranty period is based on national regulations and can be found at www.alturos.com/agb/.

Subject to all contractually agreed warranty and liability provisions, warranty and liability claims are excluded in the following cases:

- Improper use of devices
- Improper installation
- Lack of appropriate safety measures and warnings in the danger zone
- Irregular or insufficient maintenance
- Use of material not specified and tested by Alturos
- Lack of structural renovation measures
- Insufficient training of operators
- All structural, technical or other changes; interventions and/or additions to the system without the express consent of Alturos Destinations GmbH
- Disasters caused by external events and force majeure

This user manual must be read carefully before starting any work on and with the product! The manufacturer accepts no liability for damage and malfunctions resulting from non-observance.

The textual and pictorial representations do not necessarily correspond to the scope of delivery. The illustrations and graphics do not correspond to the scale 1:1. The actual content of the delivery may deviate from the information and notes described here and from the illustrations in the case of special versions, the use of additional ordering options or due to the latest technical changes.

If you have any questions, please contact **Alturos Destinations Customer Service**.

We reserve the right to perform technical modifications to the device in the course of improving its usage properties and further development.

2.2 Appropriate use

Appropriate use also includes correct compliance with the operating conditions and the information and instructions in this user manual. The device may only be operated with parts and original accessories supplied by the manufacturer.

2.3 Modifications and changes to the device

In order to avoid hazards and to ensure optimum performance, no modifications, additions or alterations may be made to the device that have not been explicitly approved by the manufacturer.

All pictograms, signs and inscriptions on the device must be kept in a clearly legible condition and must not be removed. Damaged or illegible pictograms, signs and inscriptions must be replaced immediately.

2.4 Staff requirements

The following activities may only be performed by **authorised and instructed** staff.

Responsibilities for working on and with the device must be clearly defined and complied with.

Do not work in any way that may compromise the safety of persons, the environment or the device.

Education	Definition
instructed person	An instructed person is a person who has been informed about the assigned tasks and possible dangers in case of improper behaviour and, if necessary, has been trained and instructed about the necessary protective equipment and protective measures.
trained user	A trained user is someone who fulfils the requirements for an instructed person and has also received system-specific training from Alturos Destinations or an authorised distributor.
Qualified specialist	A qualified specialist is defined as someone who, on the basis of his training, knowledge and experience and knowledge of the relevant regulations, is able to assess the work assigned to him and recognise possible hazards. Several years of activity in the relevant field of work may also be taken into account for the assessment of the technical training.
Qualified electrician	Due to their professional training, knowledge and experience as well as their knowledge of the relevant standards and regulations, qualified electricians are able to carry out work on electrical systems or equipment and to independently identify and avoid possible hazards. The qualified electrician has been specially trained for the working environment in which he/she works and knows the relevant standards and regulations. The qualified electrician must comply with the regulations of the applicable statutory accident prevention rules and regulations.
Customer Service	Customer service is defined as service technicians who have been trained and authorised by Alturos Destinations to work on the system or equipment.



The staff is obliged to immediately report any changes to the device that impair safety to the customer!

2.5 Safety at work

By following the specified safety instructions and instructions in this technical manual, personal injury and damage to property during work with and on the device can be avoided. Non-observance of these instructions can lead to danger to persons and damage or destruction of the installation.

In case of non-compliance with the safety instructions and instructions given in this manual as well as the accident prevention regulations and general safety regulations applicable to the area of application, any liability and damage claims against the manufacturer or his authorised representative are excluded.

Risk of injury due to the heavy weight of the equipment! Installation work must only be carried out with suitable lifting gear! All electrical connections and repair work on the units may only be carried out by a qualified electrician. The following rules must be observed before connecting the equipment:

1. *Disconnect mains!*
2. *Prevent reconnection!*
3. *Test for absence of harmful voltages!*
4. *Ground and short circuit!*
5. *Cover or close off nearby live parts!*




Hazard! *Danger due to electric current: The electrical energy can cause extremely serious injuries. If the insulation or individual components are damaged, there is a danger to life from electric current.*

After completion of work, these steps are carried out in reverse order.

3 Technical specifications

3.1 Overview



The equipment of the Skiline terminal may vary depending on the variant!

3.2 Data tableTerminal

Parameter	Value
Dimensions	80x43x24cm
Weight	36kg
Supply voltage	230 V AC / 50 Hz
Internal low voltage supply	24 V DC / 240W
Power input	280 Watt at maximum load
Case	<i>Material: stainless steel</i> <i>Surface: powder coating RAL 9010 (standard)</i> <i>Front pane: ESG glass anti-reflective</i>
Protection class by casing according to EN 60529	IP34
Temperature range	<i>Storage: -40°C to +70°C</i> <i>Operation: -20°C to +40°C</i>
Data interface	RJ45 Ethernet connection
Thermal Printer	<i>Consumables:</i> <ul style="list-style-type: none"> • 3" / 80mm thermal paper 65 to 150µm • rollers Ø max. 200mm • Roller core Ø12 or Ø50mm depending on the model. printing speed: max. 200mm/s
Display	<i>Size: 24" color TFT LCD display in portrait format</i> <i>Brightness: 1500 cd/m²</i> <i>Resolution: Full HD 1920x1080p</i>
Touchscreen	PCT Single Touch
RFID reader	<i>Operating concept: HF short-range RFID USB module</i> <i>Working frequency: 13,56 MHz</i> <i>reading range: up to 80mm</i> <i>RFID protocols: ISO 15693 incl. special functions</i>
Barcode reader	<i>Compatibility: 2D Barcodes and QR Codes</i> <i>Lighting: LED white</i> <i>Crosshair: Laser Class 2 IEC 60825</i>
Webcam	<i>Resolution: 1920 x 1080p configurable for landscape or portrait</i>

Heating	<i>100W PTC thermistor heater (PTC) optional</i>
Fan	<i>80x80 resp. 60x60 24V</i> <i>Insect guards on the fan gills</i>
Sound (option)	<i>Power: 30W</i> <i>Waterproof IP65 8cm speaker</i>

3.3 Data table Photo Pickup Modul


Parameter	Value
Dimensions	80x43x24cm
Weight	54kg
Supply voltage	230 V AC / 50 Hz
Internal low voltage supply	24 V DC / 65W
Power input	450 Watt at maximum load
Housing	<i>Material: stainless steel</i> <i>Surface: powder coating RAL 9010 (standard)</i> <i>Front pane: ESG glass anti-reflective</i>
Protection class by casing according to EN 60529	IP34
Temperature range	<i>Storage: -40°C to +70°C</i> <i>Operation: +5°C to +35°C</i>
Data interface	USB 2.0 (max. 480Mbit/s) Connection Typ B
Photoprinter	<i>Capacity: aprox. 200 sheets</i> <i>Standard resolution: (600dpi)</i> <i>Print speed: 23,6 dot/mm</i> <i>Print dimension: 152 mm x 203 mm (6x8") [2PC]</i>
Heating	20W thermistor heater (PTC) 50W thermistor heater (PTC) 250W heater
Fan	80x80 resp. 60x60 24V <i>Insect guards on the fan gills</i>
Payment modules	<i>Slot card reader</i> <i>Keyboard</i> <i>Contactless reader</i>

3.4 Type plate

Supply voltage

Part number

Max. device power




Description


Serial number

4 Operation terminal

4.1 Opening the device




Unlock the door with the provided keys.



Pull down door latch.



Be careful when opening the latch to avoid scratches on the bottom side of the housing!



Turn door latch by 90° to the frontside and open the door.

NOTICE


When opening the device in horizontal position, no load must be transferred to the door!

CAUTION

Caution Risk of injury from falling terminal due to the changed center of gravity!

4.2 Close the device

The device is closed in the reverse order to that described in section 4.1. described.




4.3 Switching the device on and off

Open the device as described in chapter Fehler! Verweisquelle konnte nicht gefunden werden..



Initial commissioning may only be carried out by qualified technicians.



- Turn the circuit breaker upwards to switch it on.
- Turn the circuit breaker down to switch it off.



Before intentionally shutting down the device for a long time, remove the printer paper and inform the technical support.

4.4 Changing the thermal paper roll



Thermal paper requirements:

Width 80mm (3inch) | Thickness 65 to 150µm | Thermal print layer Outer
innerØ min. 12mm | outerØ max. 200mm




Fire hazard: Do not store spare paper rolls in the housing, as some components can become very hot.


4.4.1 OPENING THE DOOR

Open the device as described in chapter **4.1**.

4.4.2 REMOVE EMPTY ROLL



4.4.3 OPEN PRINTER FLAP




Open the printer flap on the right side by lifting the latch.

Carefully open the printer flap to the left.
(yellow)




Check whether there are paper residues in the bezel funnel (black arrow)!

4.4.4 CLOSING THE PRINTER FLAP




4.4.5 INSERTING THE NEW THERMOROLL




Insert a new thermal paper roll into the printer with the start of the paper at the front (orange arrow).

4.4.6 INSERT PAPER




Inserting the thermal paper into the slot of the printer - it automatically feeds the paper, prints "TEST PRINT" and cuts off the test paper.

4.4.7 REMOVE TEST PRINT SECTION



Be sure to remove test print section!

4.4.8 CLOSE THE DOOR



Schematic representation of a correctly inserted paper roll.



Schematic representation Bezel funnel



Then close the device again as described in section **4.2**

4.5 Maintenance screen

After switching on the device, the maintenance screen appears when the door is open, which is necessary for the further steps of commissioning. The maintenance screen provides information about system-relevant data and is required for the network configuration; in addition, test prints can be performed here.



The design of the maintenance screen can vary depending on the equipment!


4.5.1 LANGUAGE

The language can be set in the lower part of the maintenance screen, English, French, Italian and German are available.




4.5.2 SYSTEM DATA

The **SYSTEM DATA** field provides system-relevant data for the operation of the device. A constant temperature in the device is crucial for trouble-free operation.



4.5.3 NETWORK CONFIGURATION

The configuration of the network can be done in the **SETTINGS** field.



NETWORK CONFIGURATION

DHCP ☒

IP address

Netmask

Gateway

DNS

MAC address

skiline.cc ☒

Device management ☒

VPN server ☒

System date

The data is entered via the integrated touch screen function.

If the device is in a network with DHCP, the network configurations are automatically assigned to the device, so no further network settings are necessary.

The following steps must be carried out during network configuration:


1. Enter network data.
2. Press the **APPLY** button after the entry is complete.
3. Perform network test by pressing the **TEST** button.

NOTICE

The network configuration may only be carried out by qualified staff!


4.5.4 OUT OF ORDER MODE

If the device is in "Out of order" mode, it is no longer possible to use it in operation. This mode can be switched on and off in the bottom field of the maintenance screen. If the slider is moved to the right, the dot appears in green, so the out of order mode is activated, for deactivation the slider must be moved to the left again.



4.5.5 TEST PRINT


One print can be performed in each of the two "**PERFORM TEST PRINT**" fields in order to test the function of the installed thermal printer. Make sure that the paper is properly inserted.



For information about loading paper rolls, please refer to the enclosed User manual.

4.5.6 BARCODE READER TEST

Via the "**Barcode reader**" field, a QR code can be read out via a test printout (short) printed on the thermal printer.



QR-/Bar-Code-Number: _____

Start reader

The image shows a dark gray rectangular interface with a white border. At the top center, there is a small white triangle pointing downwards. On the left side, the text "QR-/Bar-Code-Number:" is followed by a long horizontal white line for input. On the right side, there is a rounded rectangular button with the text "Start reader".

4.5.7 RFID READER TEST

Via the field "**RFID reader**" a key card number can be read from a RFID ticket.



Keycard-Number: _____

Start reader

The image shows a dark gray rectangular interface with a white border. At the top center, there is a small white triangle pointing downwards. On the left side, the text "Keycard-Number:" is followed by a long horizontal white line for input. On the right side, there is a rounded rectangular button with the text "Start reader".

4.6 Remote access

The following settings can be configured remotely by an Alturos employee:

- General backlight setting of the display.
- Configuration of 2 different backlight settings depending on daytime.
- Display switch-off times.



The remote setting options can vary depending on the equipment.



Configuring switch-off times saves resources and can increase the service life of display and cooling components.




Alturos can put the device into "out of order" mode, switch it off completely or restart it, and receive software updates.

5 Operation Photo Pickup Modul


5.1 Open the device




Open the lock with the provided keys.



Pull down latch.



Swivel the lever 90° to the front - the removal flap opens a bit



Open the door

5.2 Close the device

The device is closed in the reverse order to that described in section **5.1**.

5.3 Loading paper and ribbon



Only media (paper and ribbon) approved by DNP for this type of printer may be used.



The media size must not be changed without consulting Alturos.




Attention: When installing the device outdoors, be sure to consider weather conditions before changing media. Snow or wet conditions on the media can damage it and will affect the quality of the printed photos. Strong winds can make it difficult to load the ribbon or damage it!

5.3.1 OPEN THE DEVICE

Open the device as described in section 5.1.


5.3.2 PULLING OUT THE PRINTER



Pull out the printer forward until it stops.



Follow instructions from the DP DS620 user manual starting on page 12.



Push the printer into the housing as far as it will go.




The printer connection cables must not be pinched under any circumstances!



2 sets are included per media set (reserve paper + ribbon) - the reserve media set can be placed on a platform in the Photo Pickup module. This is especially recommended at low outside / storage temperatures, as the temperature of the media set can assimilate in this way.



Do not open the airtight packaging of the ribbon when stored in the housing!



Reserve media can be stored in the top left of the device.

Close the device as described in section 5.2.


5.4 Maintenance screen



The design of the maintenance screen may vary depending on the equipment



As soon as the photo pickup module is opened, the device switches to maintenance mode and the following screen appears on the terminal display



The following activities are performed via the maintenance screen:

- Perform test print
- Out of order mode
- Watch the instruction video on how to change media

In addition, the number of printable photos until the next media change can be read off and the error display of the photo printer can be read off.

Green=

No activity required

Yellow=


Activity required soon
(refilling or cleaning)

Red=

Urgent action required


5.4.1 SYSTEM DATA

The **SYSTEM DATA** field provides system-relevant data for the operation of the device. A constant temperature in the device is crucial for trouble-free operation.




5.4.2 LANGUAGE

The language can be set in the lower part of the maintenance screen, English, French, Italian and German are available.



5.4.3 TEST PRINT

The "**Print Test**" button can be used to perform a test. These are usually carried out after the photos have been filled to ensure that they function correctly.




5.4.4 OUT OF ORDER MODE

If the device is in "**Out of order**" mode, it is no longer possible to use it in operation. This mode can be switched on and off in the bottom field of the maintenance screen. If the slider is moved to the right, the dot appears in green, so the out of order mode is activated, for deactivation the slider must be moved to the left again.



5.4.5 INFORMATION PHOTOPRINT

All information on paper status, printer status and current firmware versions can be retrieved via the "Photo Printer" button.



5.5 Cleaning



*It is strongly recommended to perform cleaning **BEFORE** busy days!*

Part	Intervall	Cleaning	Figure
Photoprinter	When changing media	Disposing of the paper scraps	User manual DP-DS620 Page 18
Photoprinter	If an indent or lines are visible at regular intervals on the printouts (approximately every 50 mm) or if the back of the printouts (white page) is dirty.	Cleaning the print roller	User manual DP-DS620 Page 24
Photoprinter	If stains adhere to the thermal printhead, bumps or gaps could appear during printing.	Cleaning thermal printhead	User manual DP-DS620 Page 25
Extraction tray	Weekly	Cleaning wipe	

6 Troubleshooting



At low outdoor temperatures, the vending machine can remain in "out of service" mode for up to approx. 1h after start-up.



Diagnosis: *As soon as "Out of service" or "In maintenance" appears on the display, the maintenance screen of both modules can provide information*

Problem	Root cause	Corrective action
Photoprint machine remains in "Out of order" mode after power on	Interior temperature too low	Checking the interior temperatures of the Photo Pickup module via maintenance screen (see point 5.4)
Paper jam thermal printer in terminal module	Ejector compartment clogged or overfilled	<ol style="list-style-type: none"> 1. open terminal module 2. check the ejection tray and if there is too much paper or paper is stuck, remove paper 3. Start test print via maintenance screen (see section 5.4.3)
Paper jam thermal printer in terminal module	Funnel clogged or overfilled	<ol style="list-style-type: none"> 1. Open the terminal module 2. Check whether there is paper residue in the funnel (see chapter 4.4.7) 3. Start test print via maintenance screen (see 5.4.3)
Paper jam thermal printer in terminal module	Paper roll inserted crooked	<ol style="list-style-type: none"> 1. Open the terminal module 2. check if paper roll is inserted correctly (see 4.4.5) 3. Start test print via maintenance screen (see 5.4.3)
Thermal paper is not printed	Paper roll inserted incorrectly	<ol style="list-style-type: none"> 1. Open terminal module 2. check if paper roll is inserted correctly (see 4.4.5) 3. start test print via maintenance screen (see 5.4.3)
Touchscreen does not respond	Dirt on the touchscreen surface	Visually check whether there is any dirt on or behind the touch surface and clean with glass cleaner and microfiber cloth if necessary.
Touchscreen does not respond	System does not respond	Switch the device off and on (see 4.3)
Touchscreen does not respond	Touchscreen defective	Contact customer service
Display fault	Temperatures too high	<ol style="list-style-type: none"> 1. If the temperature on the display is too high, it is automatically switched off. The remaining systems, especially the air conditioning components, remain active to dissipate the heat. As soon as the operating

		<p>temperatures are reached again, the display is automatically switched on again.</p> <p>2. In case of abnormal artifacts, unusual color changes or too weak backlight, please contact support.</p>
Fogged display on the inside	Interior humidity	<p>1. Check if the device is closed correctly</p> <p>2. Temperature status terminal module via maintenance screen (see 5.4)</p> <p>3. If the problem could not be solved contact customer service</p>
Network error	On-site network malfunction	<p>1. Check network status terminal module via maintenance screen (see 5.4)</p> <p>2. Contact facility management</p>
Network error	System does not respond	<p>1. Check network status terminal module via maintenance screen (see 5.4)</p> <p>2. Terminal module switch off and on (see 4.3)</p> <p>3. If the problem could not be solved contact customer service</p>
Aborted payments	Incorrect or blocked means of payment	<p>1. Control of the reports on the screen of the payment modules</p> <p>2. Kontrolle des Zahlungsmittels</p>
Aborted payments	System does not respond	<p>1. Check status terminal module via maintenance screen (see 5.4.1)</p> <p>2. If the problem could not be solved contact customer service</p>
Missing payment receipt	Problems with thermal printer	Check paper and thermal printer
Particles of dirt on the printed photo	Overfilled paper cuttings waste box	See instructions in the DP-DS620 user manual page 18
Long waiting times for photo printing	Overheated printhead	Control printer status via the maintenance menu (see 5.4)
Photo printer paper error	Paper jam in printer	See instructions in the DP-DS620 user manual page 20
Ribbon error in photo printer	Ribbon caught in the printer	See instructions in the DP-DS620 user manual page 22
Partially cut paper in paper tray	Plugging cutting knife	See instructions in the DP-DS620 user manual page 23
Main compartment of the photo printer does not open	Power supply was interrupted during printing	See instructions in the DP-DS620 user manual page 23

7 Value preservation

- Perform regular visual checks on the overall condition of the device.
- Perform touch screen test across the entire surface.
- Check display for abnormal artifacts or unusual color changes.
- Check for moisture in the interior and insect infestation.

Clean the housing only with non-aggressive cleaning products (e.g., warm soapy water). Clean the glass front regularly with glass cleaner and microfiber cloth.

If the device is to be taken out of operation, switch it off (see chapter 4.3) and protect it with a cover.



Fire hazard: *Do not cover the device when switched on!*

8 Support

Our customer service / technical support is available as follows:

Adress:	Alturos Destinations GmbH Am Bach 4 A-6840 Götzis
Phone:	+43 463 249 445-880
Mail:	b2b-support@skiline.cc
Web:	www.alturos.com

In addition, we are always interested in information and experiences that result from the application and can be valuable for the improvement of our products.

9 Disassembly & disposal

9.1 Disassembly

Disassembly must be carried out by a qualified technician. The device and all operating materials must be disposed of properly.

9.2 Disposal

At the end of the device's service life, it must be disposed of by a qualified company. In exceptional cases and after consultation with Alturos Destinations GmbH the device can be returned.



Risk to the environment: *Incorrect disposal can pose risks to the environment.*



Attention: *Electrical waste, electronic components, lubricants and other additives are subject to hazardous waste treatment and may only be disposed of by authorized companies!*

The local municipal companies can provide information on environmentally friendly disposal.